Amendments to the Claims

- 1. (Currently Amended) A borosilicate glass with a composition in a percent by weight on an oxide basis, including: 60 75% SiO₂, 10 15% B₂O₃, 5 15% Na₂O, 5 10% K₂O, 0.1 1% CaO, 0.5 3% BaO, > 0 1.7% TiO₂, 0 0.5% Sb₂O₃, and normal refining agents, and having an edge wavelength λ_c between 280 nm and 325 nm and a pure transmission degree of τ_{ip} in a pass range of greater than 98% and an optical density in a stop range of 1 x 10⁵ with a sample thickness of 2 mm.
- 2. (Currently Amended) A borosilicate glass according to claim 1, wherein the composition in the percent by weight on the oxide basis includes 65 75% SiO₂, 10 13% B₂O₃, 6 12% Na₂O, 5 10% K₂O, 0.1 0.5% CaO, 0.5 2.5% BaO, \geq 0 1.7% TiO₂, 0 0.5% Sb₂O₃, and normal refining agents.
- 3. (Currently Amended) A borosilicate glass according to claim 2, wherein the composition in a second the percent by weight on a second the oxide basis further includes 0.5 2.5% SrO, 0.1 1% MgO, and 0 5% Li₂O.
- 4. (Original) A borosilicate glass according to claim 3, wherein the composition is free of As₂O₃, PbO and CeO₂, apart from unavoidable impurities.

5. (Canceled)

6. (Currently Amended) A borosilicate glass according to claim [[5]] 4, having an edge situation wherein the edge wavelength is in a range

Serial No. 10/675,224

between 280 to 295 nm, and a TiO₂ content of greater than 0 to 0.1% by weight on an oxide basis.

- 7. (Currently Amended) A borosilicate glass according to claim [[5]] 4, having an edge situation wherein the edge wavelength is in a range between 290 and 305 nm, and a TiO₂ content of 0.05 to 0.3% by weight on an oxide basis.
- 8. (Currently Amended) A borosilicate glass according to claim [[5]] 4, having an edge situation wherein the edge wavelength is in a range between 300 to 315 nm, and a TiO₂ content of 0.16 to 0.8% by weight on an oxide basis.
- 9. (Currently Amended) A borosilicate glass according to claim [[5]] 4, having an edge situation wherein the edge wavelength is in a range between 310 to 325 nm, and a TiO₂ content of 0.5 to 1.7% by weight on an oxide basis.
- 10. (Currently Amended) A borosilicate glass according to claim 9, used for producing filter glass for wherein the glass comprises a UV cut-off filters filter in at least one of a UVB range and a UVC range.
- 11. (Currently Amended) A borosilicate glass according to claim 10, used for producing wherein the glass comprises a filter glass for one of illumination tables and weathering instruments.
- 12. (Currently Amended) A borosilicate glass according to claim 10, used for producing wherein the glass comprises an optical glass for

VO-659 5 MDS/S

imaging optics, projection, telecommunications, optical telecommunications technology and microlithography.

- 13. (Currently Amended) A borosilicate glass according to claim 12, having a transformation temperature Tg greater than 560°C, with a thermal expansion coefficient $\alpha_{(20/300)}$ between 7.5 and 8.8 [[*]] \underline{x} 10⁻⁶/K, and \underline{a} steep edge situations wavelength between 275 nm and 325 nm.
- 14. (Currently Amended) A borosilicate glass according to claim 1, wherein the composition in a second the percent by weight on a second the oxide basis further includes 0.5 2.5% SrO, 0.1 1% MgO, and 0 5% Li₂O.
- 15. (Original) A borosilicate glass according to claim 1, wherein the composition is free of As₂O₃, PbO and CeO₂, apart from unavoidable impurities.

16. (Canceled)

- 17. (Currently Amended) A borosilicate glass according to claim 1, having an edge situation wherein the edge wavelength is in a range between 280 to 295 nm, and a TiO₂ content of greater than 0 to 0.1% by weight on an oxide basis.
- 18. (Currently Amended) A borosilicate glass according to claim 1, having an edge situation wherein the edge wavelength is in a range between 290 and 305 nm, and a TiO₂ content of 0.05 to 0.3% by weight on an oxide basis.

- 19. (Currently Amended) A borosilicate glass according to claim 1, having an edge situation wherein the edge wavelength is in a range between 300 to 315 nm, and a TiO₂ content of 0.16 to 0.8% by weight on an oxide basis.
- 20. (Currently Amended) A borosilicate glass according to claim 1, having an edge situation wherein the edge wavelength is in a range between 310 to 325 nm, and a TiO₂ content of 0.5 to 1.7% by weight on an oxide basis.
- 21. (Currently Amended) A borosilicate glass according to claim 1, used for producing filter glass for wherein the glass comprises a UV cut-off filters filter in at least one of a UVB range and a UVC range.
- 22. (Currently Amended) A borosilicate glass according to claim 1, used for producing wherein the glass comprises a filter glass for one of illumination tables and weathering instruments.
- 23. (Currently Amended) A borosilicate glass according to claim 1, used for producing wherein the glass comprises an optical glass for imaging optics, projection, telecommunications, optical telecommunications technology and microlithography.
- 24. (Currently Amended) A borosilicate glass according to claim 1, having a transformation temperature Tg greater than 560°C, with a thermal expansion coefficient $\alpha_{(20/300)}$ between 7.5 and 8.8 [[*]] \underline{x} 10⁻⁶/K, and \underline{a} steep edge situations wavelength between 275 nm and 325 nm.